


EXPLOSION PROOF CCTV

CNEx Explosion Proof IP68 CCTV Housing




ZAF1032C

Explosion Proof CCTV IR Fixed Camera Housing




PT. BERSAUDARA MANDIRI REJEKI

Jl. Cisaranten Baru No.57, Cisaranten Kulon
Arcamanik Kota Bandung, 40293
Telp : (022) 63745201 WhatsApp : 0812-2220-6505
Email : sales@fnrgrup.com
<https://www.bersaudaramandiri.co.id>



CNEx Explosion Proof IP68 CCTV Housing

Explosion Proof CCTV IR Fixed Camera Housing



Description :

Dengan Sertifikasi yang ketat, Housing ini dirancang untuk digunakan dalam area berbahaya kimia, fasilitas gas dan oli, pabrik pengolahan makanan, dan area berbahaya lainnya, untuk mencegah kerusakan pada peralatan camera dengan menahan panas, percikan api atau api yang dihasilkan, serta suhu yang panas dari luar housing.

Material SS 316L dapat digunakan untuk marine seperti kapal laut, rig offshore, dan industri maritim lainnya.

Working Environmental Condition :

- Working Voltage : AC100-240V
- Working Electric Current : $\leq 1000\text{mA}$
- Environment temperature : $-25^{\circ}\text{C} \sim +60^{\circ}\text{C}$
- Average relative humidity : $\leq 95\%$
- Atmospheric Pressure : $80\text{kPa} \sim 106\text{kPa}$
- Apply to explosive gas atmosphere 1 district / 2 district dangerous ground
- Apply to IIA, IIB, IIC grade explosive gas atmosphere
- Apply to flammability dust environment 20/21/22 district
- Apply to the environment of temperature group T1-T6

Features :

- CNEx, CE, Approved
- Applicable for Gas Zone 1, Zone 2, (Class IIA, IIB, IIC, T1-T6 group) Dust Zone 21, 22.
- Stainless steel 304 or 316L enclosure
- Surface optional electro-polished or painting
- Weather Proof Ip68 (1.2m/45min)
- Wide voltage input: AC100-240V or AC24V
- Strong tempered glass, fit for hydrofluoric acid area
- Intelligent window defroster design
- Auto temperature adjust kit for aggressive area
- High precision wiper, support user-defined
- Auto temperature adjust kit for aggressive area
- Symmetrical balancing design
- Intelligent long focal speed limit, fit for long distance monitoring



Certificate

Certificate Mark	Exd II C T6 Gb / Ext D A21 IP68 T80℃
Certificate No	CNEx16.2693X
Standards	Q/320412ZAF032-2016

Mechanical

Housing	Stainless steel 304 or 316L
IP	IP68
Cable thread hole	2pcs G3/4 or NPT3/4
Sun-shield	No
Wiper	No

Electrical

Voltage	AC100-240V, AC24V, 50/60Hz or POE
Power	15W/25W (with thermostat)

Ambient

Ambient temperature	-20 to +60℃ / -45 to +80℃
Air pressure	80Kpa to 106Kpa
Relative Humidity	≤95% (no condensation)

Lights

Infrared Light Distance	50m
Lights Control	Support



ZAF1032C



CNEx Explosion Proof IP68 CCTV Housing

Explosion Proof CCTV IR Fixed Camera Housing

General

Cable	integrated cable
Inner Size for Camera	210*80*80 mm
Overall Dimension	416.5*166*258 mm
Net Weight	12kg
Mounted	Wall, Pole
Wall Bracket	ZAZ100B



Relative Product



ZAZ100B



ZAZ100PMB




ZAZ100C



ZANXG






ZA-JXD4Ex Junction box



CZ300 Ex Control Box

Dimension





CONTACT PERSON



PT. BERSAUDARA MANDIRI REJEKI



Jl. Cisaranten Baru No.57, Cisaranten Kulon
Arcamanik Kota Bandung, 40293
Telp : (022) 63745201
WhatsApp : 0812-2220-6505
Email : sales@fnrgrup.com



国家防爆

